

Corbreak Data Sheet



Corbreak is a unique system to aid the trimming down of piles. During the construction of piled foundations, it is quite often necessary to reduce the height of the piles and expose the reinforcement within them. The removal of concrete required to do this has been traditionally carried out using hand held tools which subject the users to a number of health and safety related issues e.g. noise and vibration.

Corbreak units are a fast, quiet and economic solution to the problems associated with the trimming down of piles. Manufactured from Filcor EPS, they are fixed into the pile reinforcement cage prior to placing the cage into the bore. After casting of the pile and the exposure of the top of the pile shaft the Corbreak allows the top of the pile to be cracked and lifted off thereby reducing the height of the pile to the required level.

Key Features

- Manufactured from a lightweight Filcor EPS
- No chemicals required during the installation or removal process
- Reduces the breaking out time when compared to traditional methods
- Removal can be carried out quietly, without the need for hand held tools
- Avoids the risk of cracking the pile when using heavy hydraulic breakers

Installation

Each Corbreak unit is typically positioned over the vertical pile reinforcement, approximately 30mm above the proposed trim level of the pile. It is held in position with the application of expanding foam around the reinforcement.

Following positioning of the Corbreak unit, de-bonding sleeves are placed over the reinforcement bars and the pile cage is lowered into the ground. Concrete is then poured through the central opening in the Corbreak unit it has reached the height of the projecting rebar.

Following curing, the central 'plug' of concrete can be easily detached and mechanically lifted off the top of the pile.

Storage & Handling

Individual units can be manually handled and offloaded upon delivery.

Due to the relatively light nature of the product, all Cordek Corbreak units should be weighted down or secured should they be stored outside prior to installation. No further storage requirements are needed as the product is unaffected by both UV light and water.

For further information on the full range of Cordek's Piling Products, please contact the Cordek technical team on 01403 799600, techsupport@cordek.com or consult our website at www.cordek.com.



Product Data

Unit Dimensions:

Diameter – Ranges from 1.0m to 2.5m depending on diameter of pile

Depth – Varies based upon the diameter of the Corbreak units

Hole Diameter / Spacing:

As required to suit the reinforcement diameter and layout

Materials:

Filcor EPS faced with Correx (Polypropylene Sheet) to aid rigidity and reduce adhesion

Issued: 04/2015

DISCLAIMER: Information contained within this 'Technical Data Sheet' is for guidance only, and it is intended for experienced construction industry workers. It contains summaries of aspects of the subject matter and does not provide comprehensive statements of construction industry practice. As conditions of usage and installation are beyond our control we do not warrant performance obtained. Please contact us if you have any doubt as to the suitability of application. The information provided within this document is based on data and knowledge correct at the time of printing.

Cordek Ltd

Spring Copse Business Park, Slinfold, West Sussex
RH13 0SZ, United Kingdom

Telephone (+44) 1403 799600 Fax (+44) 1403 791718
E-mail info@cordek.com

www.cordek.com

