

# Sacrificial Guide Wall Formers Data Sheet



Sacrificial Guide Wall Formers are used to accurately form an insitu concrete guide wall which is critical in the positioning and alignment of piles in a contiguous or secant piled wall.

From a customer's pile layout drawing Cordek will produce a drawing detailing the size, shape and position of each former. After customer approval of the layout drawing each former is CNC cut from a solid block of Filcor expanded polystyrene.

The formers are single use only, they are not designed to be struck from the finished guide wall as the nature of the Filcor material allows the piling rig to auger straight through the formers.

## Key Features

- Improves the accuracy of pile guide wall construction
- Can be used with both secant and contiguous pile wall constructions
- Manufactured from a low density polystyrene for a cost effective solution
- Can accommodate most pile designs, including curved and circular pile walls
- Quick and easy to install for rapid guide wall construction

## Installation

Each pile locator should be accurately positioned on a flat level surface. They should be secured in position so that they do not get displaced during the concreting of the guide wall.

## Storage & Handling

Individual units can be manually handled and offloaded upon delivery subject to established risk assessment criteria.

Due to the relatively light nature of the product, all Cordek Pile Locators units should be weighted down or secured if they are to be stored outside prior to installation. No further storage requirements are needed as the product is unaffected by both UV light and water.

For further information on the full range of Cordek's Piling Products, please contact the Cordek technical team on 01403 799600, [techsupport@cordek.com](mailto:techsupport@cordek.com) or consult our website at [www.cordek.com](http://www.cordek.com).



## Product Data

**Former Dimensions:** Typically supplied 2.4m lengths but this may vary depending on pile centres. Depth to suit customer specifications but typically 600mm, 800mm or 1000mm deep

**Materials:** Cordek Filcor EPS

**Issued: 04/2015**

DISCLAIMER: Information contained within this 'Technical Data Sheet' is for guidance only, and it is intended for experienced construction industry workers. It contains summaries of aspects of the subject matter and does not provide comprehensive statements of construction industry practice. As conditions of usage and installation are beyond our control we do not warrant performance obtained. Please contact us if you have any doubt as to the suitability of application. The information provided within this document is based on data and knowledge correct at the time of printing.

**Cordek Ltd**

Spring Copse Business Park, Slinfold, West Sussex  
RH13 0SZ, United Kingdom

Telephone (+44) 1403 799600 Fax (+44) 1403 791718  
E-mail [info@cordek.com](mailto:info@cordek.com)

[www.cordek.com](http://www.cordek.com)

