


Standard Detail



Tel : 01403 799600
 Email : techsupport@cordek.com

Drg. Title:
 Cordek VOC / Hydrocarbon Protection System
 Typical Ground Slab with Perimeter Thickening Detail

Drawn: JP

Date: Nov.2023	Scale: NTS
Drg. No. ENG/GP/MEM/PUR/03	Rev: C

Materials :-	Notes :-
<p>Refer to Cordek technical data sheets for full detailed material specification</p> <p>A. Cordek Puraflex Membrane B. Cordek Double Sided Jointing Tape C. Cavity tray by others</p> <p>NB : Cordek Puraflex should be installed with welded joints only. Vertical membrane to be mechanically fixed to Cordek recommendations</p>	<ul style="list-style-type: none"> - This detail is issued for guidance purposes only, with final approval required from the designer - Do not scale from drawing, use dimensions provided - All laps and junctions must be fully sealed with appropriate welding techniques or jointing system - The intended construction sequence should be considered prior to selection of the appropriate Cordek standard detail to ensure that installation is practical and achievable - In accordance with BS8102:2009, should hydrostatic water pressure be a risk, additional waterproofing methods should be considered - In line with industry guidance and good practice, a sub-floor venting layer should be considered - please consult Cordek for further advice