

Metsec or similar metal stud framing system

FFL

150

GL

Materials :-

Refer to Cordek technical data sheets for full detailed material specification


A. Cordek Puraflex Membrane
 B. Cordek Double Sided Jointing Tape
 C. VCL / floor finishes by others
 D. Cavity tray by others

NB : Cordek Puraflex should be installed with welded joints only.
 Vertical membrane to be mechanically fixed to Cordek recommendations

Notes :-

- This detail is issued for guidance purposes only, with final approval required from the designer
- Do not scale from drawing, use dimensions provided
- All laps and junctions must be fully sealed with appropriate welding techniques or jointing system
- The intended construction sequence should be considered prior to selection of the appropriate Cordek standard detail to ensure that installation is practical and achievable
- In accordance with BS8102:2009, should hydrostatic water pressure be a risk, additional waterproofing methods should be considered
- In line with industry guidance and good practice, a sub-floor venting layer should be considered - please consult Cordek for further advice

Standard Detail



Tel : 01403 799600
 Email : techsupport@cordek.com

Drg. Title:
 Cordek VOC / Hydrocarbon Protection System
 Typical RC Slab Edge Detail - SFS System

Drawn: JP

Date: Nov.2023 Scale: NTS

Drg. No. ENG/GP/MEM/PUR/07 Rev: C