


Products :-	Notes :-	Standard Detail				
Filcor EPS.	<ul style="list-style-type: none"> - All Filcor material is manufactured in accordance with EN 14933:2007. - The Filcor material should be supported on a firm, level surface. - If the applied load exceeds the theoretical compressive strength at 1% strain then the strain will potentially exceed 1% (the assumed elastic limit) and the amount of deflection should be considered. - Where the depth of Filcor requires multiple layers, each subsequent layer should be laid perpendicular to the one below, with all joints equally staggered. - Where the void former is required to act as insulation to the structure below, the designer should consider positioning the waterproofing layer above the insulation / void former (warm roof construction) or using a moisture resistant material such as Cordek Extruded Polystyrene (XPS). - This detail is issued for guidance only, with final approval required by the designer. 	 <p>Tel : 01403 799600 Email : techsupport@cordek.com</p> <p>Drg. Title: Standard Structural Fill Beneath Soft Landscaping Detail - Filcor</p> <p>Drawn: SJP</p> <table border="1" data-bbox="1050 2101 1533 2136"> <tr> <td>Date: Feb.2018</td> <td>Scale: NTS</td> </tr> </table> <table border="1" data-bbox="1050 2145 1533 2179"> <tr> <td>Drg No. ENG/SF/FIL/003</td> <td>Rev.</td> </tr> </table>	Date: Feb.2018	Scale: NTS	Drg No. ENG/SF/FIL/003	Rev.
Date: Feb.2018	Scale: NTS					
Drg No. ENG/SF/FIL/003	Rev.					